ENTER THE STAGE.







Make Them Listen Inspire Your Audience Words Come Easy Plug'n'Play



- 04 Introduction
- 06 Vocal Set
- 08 Presentation Set
- 10 Headmic Set
- 12 Instrument Se
- 14 Technical Data



XS WIRELESS is your entry into the wireless world. Enter the stage with easy-to-use all-in-one packages offering reliable transmission and excellent sound quality. Frequency agility is ensured by a switching window of 24 MHz (13 MHz for the E band) and tunable frequency presets. The system is quick and easy to set up due to its automatic search for free frequencies and synchronization via RF remote channel. Professional True Diversity technology ensures optimum reception – anytime, anywhere.



XS WIRELESS.

For everyone who has something to say.

Vocal Set. Make Them Listen.

XSW 35/XSW 65



No matter whether you are a speaker, presenter or rocking

the stage: the XS WIRELESS VOCAL SET puts you in front of every stage. The handheld transmitter capsules offer high feedback rejection. You choose between the legendary e 835 sound (XSW 35, dynamic, cardioid) and a condenser (XSW 65, super-cardioid).

Rugged metal housing



Features

- Easy-to-use, all-in-one package for speakers, singers and presenters
- High feedback rejection
- Choice of two microphones: SKM 35 (dynamic, cardioid) or SKM 65 (condenser, super-cardioid), both with mute button for full control
- Synchronization via remote channel
- Frequencies tunable in steps of 25 kHz
- 24 MHz bandwidth (13 MHz for the E band)

- EM 10 true diversity receiver
- SKM 35 or SKM 65 handheld transmitter
- NT 2-3 mains unit
- MZQ 1 stand mount
- 2 rod antennas
- 2 AA batteries
- Pouch
- User manual

Presentation Set. Words Come Easy.

XSW 12





Almost invisible. The XS WIRELESS PRESENTATION SET is an all-in-one package – the ideal partner for impressive presentations. The professional ME 2-2 clip-on microphone, easily attached to your clothing, ensures a powerful sound transmission – and an enthusiastic audience.



Features

- Unobtrusive clip-on microphone
- High speech intelligibility
- Mute button for full speech control
- Synchronization via remote channel
- Frequencies tunable in steps of 25 kHz
- 24 MHz bandwidth (13 MHz for the E band)

- EM 10 true diversity receiver
- SK 20 bodypack transmitter
- ME 2-2 clip-on mic
- NT 2-3 mains unit
- 2 rod antennas
- 2 AA batteries
- Pouch
- User manual

Headmic Set. Inspire Your Audience.

XSW 52



Lightweight and comfortable.

The XS WIRELESS HEADMIC SET gives you absolute freedom of movement for a vivid and impressive performance. The professional ME 3 headworn microphone provides crystal-clear sound even in noisy surroundings. ME 3



Features

- Hands-free operation
- Outstanding sound quality for singers and presenters
- Mute button for full transmission control
- Synchronization via remote channel
- Frequencies tunable in steps of 25 kHz
- 24 MHz bandwidth (<u>13 MHz for the E band</u>)

- EM 10 true diversity receiver
- SK 20 bodypack transmitter
- ME 3 headworn mic
- NT 2-3 mains unit
- 2 rod antennas
- 2 AA batteries
- Pouch
- User manual

Instrument Set. Plug'n'Play.

XSW 72

Up to 10 hours of operating time

Directly connects to your guitar or instrument (¼" jack)

CL 1

SK 20

Z SENNHEISER

11

Designed for guitars and instruments with a jack socket.

The XS WIRELESS INSTRUMENT SET offers natural sound reproduction and connects your instrument directly to the bodypack transmitter – giving you the freedom to move wherever you want on stage.



Features

- Directly connects to 1/4" (6.3 mm) sockets
- Outstanding sound quality for musicians
- Mute button for full control
- Synchronization via remote channel
- Frequencies tunable in steps of 25 kHz
- 24 MHz bandwidth (13 MHz for the E band)

- EM 10 true diversity receiver
- SK 20 bodypack transmitter
- CL 1 jack cable (¼", 6.3 mm)
- NT 2-3 mains unit
- 2 rod antennas
- 2 AA batteries
- Pouch
- User manual

Technical Data

	System
Modulation	Wideband FM
Frequency range	A: 548-572 MHz GB: 606-630 MHz B: 614-638 MHz C: 766-790 MHz E: 821-832 MHz and 863-865 MHz
Switching bandwidth	24 MHz (E range: 13 MHz)
Frequencies	960 (E range: 520), tunable in 25-kHz steps; 8 frequency banks, each with up to 12 factory-preset channels
Signal-to-noise ratio	≥ 103 dBa
тно	≤ 1 %
Temperature range	0 °C to +40 °C

Transmitters

RF output power AF frequency response

AF input Nom. input voltage (Mic/Line)

Power supply Operating time Dimensions Weight Microphone type Input sensitivity Pick-up pattern Max. SPL

SK 20 bodypack

10 mW 60-16,000 Hz, Line input 100-16,000 Hz, Mic input 3.5 mm jack 0.5 Vrms/1.8 Vrms (Mic/Line) at -30 dB gain 2 AA batteries, 1.5 V up to 10 hours 66 × 96 × 24 mm 95 g — — —

Microphones

Transducer principle Sensitivity Pick-up pattern Max. SPL

ME 2-2

pre-polarised condenser 5 mV/Pa omni 142 dB

Receiver

Receiver principle Sensitivity (at peak deviation) Adjacent channel rejection Intermodulation rejection Blocking AF frequency response Pilot tone Antenna input AF output voltage (at peak dev., 1 kHz AF)

Power supply Dimensions Weight

SKM 35 handheld

10 mW 80–16,000 Hz

EM 10

True Diversity $< 3 \mu V at 52 dBa_{rms} S/N$ $\geq 60 dB$ $\geq 50 dB$ $\geq 65 dB$ 60 - 16,000 Hz 32.768 kHz $2 BNC connectors, 50 \Omega$ 1/4''' (6.3 mm) jack socket(unbalanced): +8 dBu;XLR socket (balanced): +14 dBu<math>12 VDC nom./300 mA $200 \times 42 \times 127 mm$ 730 q

SKM 65 handheld

10 mW 80–16,000 Hz

2 AA batteries, 1.5 V	2 AA batteries, 1.5 V
up to 10 hours	up to 10 hours
250 × 54 mm	250 × 54 mm
240 g	240 g
dynamic; e 835 capsule	pre-polarised conden
1.5 mV/Pa	1.8 mV/Pa
cardioid	super-cardioid
	144 dR SPI

ME 3

pre-polarised condenser 1.6 mV/Pa cardioid 150 dB iser







Sennheiser electronic GmbH & Co. KG

Am Labor 1, 30900 Wedemark, Germany

Phone +49 5130 600-0 Fax +49 5130 600-300

www.sennheiser.com